

AIP DUTCH CARIBBEAN

TNCC RNAV (GNSS) RWY 11 CODING TABLE											
<i>Fix name</i>	<i>Fix type</i>	<i>Path Terminator</i>	<i>Fly-over</i>	<i>Course °M (°T)</i>	<i>Dist NM</i>	<i>Turn dir</i>	<i>Min alt Ft</i>	<i>Max KIAS</i>	<i>Mag var</i>	<i>VPA° (TCH Ft)</i>	<i>RNP value</i>
From Puxun											
PUXUN	IAF	IF	-	-	-	-	+2500	-	+11.0	-	-
TABEB	IF/IAF	TF	-	188 (176.77)	6.0	L	2500	-	+11.0	-	1.0
From Marax											
MARAX	IAF	IF	-	-	-	-	+2500	-	+11.0	-	-
TABEB	IF/IAF	TF	-	023 (012.06)	6.0	R	2500	-	+11.0	-	1.0
From Tabeb											
TABEB	-	-	-	-	-	-	2500	-	+11.0	-	1.0
ELUVA	FAF	TF	-	113 (102.06)	5.0	-	2000	-	+11.0	-	1.0
RW11	MAPt	TF	Y	113 (102.08)	6.0	-	-	-	+11.0	-3.00 (50)	0.3
URNAP	MAHF	CF	Y	113 (102.10)	12.4	-	2500	-	+11.0	-	1.0
Other:											
1. TABEB holding inbound track 113°M (102.06°T), MNM alt 2500', MXM alt 10000', outbound 4.0 NM.											
2. URNAP holding inbound track 293°M (282.14°T), MNM alt 2500', outbound 4.0 NM.											

<i>Fix name</i>	<i>Coordinates (WGS-84)</i>
ELUVA	N12 12 42.05 W069 04 03.83
MARAX	N12 07 51.43 W069 10 20.21
PUXUN	N12 19 46.11 W069 09 24.14
TABEB	N12 13 45.07 W069 09 03.42
URNAP	N12 08 49.15 W068 45 40.27
RW11	N12 11 26.05 W068 58 03.08

CHANGES: Minimum holding altitude at URNAP.