

AIP DUTCH CARIBBEAN

TNCC RNAV (GNSS) RWY 29 CODING TABLE											
<i>Fix name</i>	<i>Fix type</i>	<i>Path Terminator</i>	<i>Fly-over</i>	<i>Course °M (°T)</i>	<i>Dist NM</i>	<i>Turn dir</i>	<i>Min alt Ft</i>	<i>Max KIAS</i>	<i>Mag var</i>	<i>VPA° (TCH Ft)</i>	<i>RNP value</i>
From Sigto											
SIGTO	IAF	IF	-	-	-	-	+2500	-	+11.0	-	-
URNAP	IF/IAF	TF	-	203 (192.14)	6.0	R	2500	-	+11.0	-	1.0
From Logla											
LOGLA	IAF	IF	-	-	-	-	+2500	-	+11.0	-	-
URNAP	IF/IAF	TF	-	023 (012.14)	6.0	L	2500	-	+11.0	-	1.0
From Urnap											
URNAP	-	-	-	-	-	-	2500	-	+11.0	-	1.0
DUKSO	FAF	TF	-	293 (282.14)	5.0	-	2000	-	+11.0	-	1.0
RW29	MAPt	TF	Y	293 (282.12)	6.0	-	-	-	+11.0	-3.00 (50)	0.3
TABEB	MAHF	CF	Y	293 (282.10)	12.4	-	2500	-	+11.0	-	1.0
Other:											
1. URNAP holding inbound track 293°M (282.14°T), MNM alt 2500', outbound 4.0 NM.											
2. TABEB holding inbound track 113°M (102.06°T), MNM alt 2500', MXM alt 10000', outbound 4.0 NM.											

<i>Fix name</i>	<i>Coordinates (WGS-84)</i>
DUKSO	N12 09 52.47 W068 50 39.72
LOGLA	N12 02 55.62 W068 46 57.53
SIGTO	N12 14 42.67 W068 44 22.95
TABEB	N12 13 45.07 W069 09 03.42
URNAP	N12 08 49.15 W068 45 40.27
RW29	N12 11 08.46 W068 56 39.69

CHANGES: Minimum holding altitude at TABEB.