

AIP DUTCH CARIBBEAN

TNCA RNAV (GNSS) RWY 11 CODING TABLE

Fix name	Fix type	Path Terminator	Fly-over	Course °M (°T)	Dist NM	Turn dir	Alt Ft/FL	Max KIAS	Mag var	VPA° (TCH Ft)	RNP value
From Igrom											
IGROM	IAF	IF	-	-	-	-	+FL40	-	+11.0	-	-
DAVLA	IF/IAF	TF	-	205 (193.59)	6.0	L	+2500	-	+11.0	-	1.0
From Elumo											
ELUMO	IAF	IF	-	-	-	-	+FL40	-	+11.0	-	-
DAVLA	IF/IAF	TF	-	025 (013.58)	6.0	R	+2500	-	+11.0	-	1.0
From Davia											
DAVLA	-	-	-	-	-	-	+2500	-	+11.0	-	1.0
BOMDA	FAF	TF	-	115 (103.60)	5.5	-	2000	-	+11.0	-	1.0
S/D fix	S/D	TF	-	115 (103.62)	3.8	-	+600	-	+11.0	-3.00 (50)	0.3
AMAVA	MAPt	TF	Y	115 (103.63)	1.5	-	-	-	+11.0	-3.00 (50)	0.3
KAPOB	MATF	DF	-	-	-	L*	-FL40	230**	+11.0	-	1.0
IGROM	MAHF	TF	-	295 (283.62)	6.4	-	FL40	-	+11.0	-	1.0

Fix name	Coordinates (WGS-84)
AMAVA	N12 30 26.16 W070 02 23.69
BOMDA	N12 31 41.97 W070 07 41.98
DAVLA	N12 32 59.81 W070 13 09.24
ELUMO	N12 27 08.32 W070 14 35.70
IGROM	N12 38 51.29 W070 11 42.72
KAPOB	N12 37 19.89 W070 05 18.39
S/D 1.5 nm to AMAVA	N12 30 47.47 W070 03 53.10

* Climb on extended CL to 800' then turn left

** Max 230 KIAS through first turn

CHANGES: altitude restriction at ELUMO.