

AIP DUTCH CARIBBEAN

TNCA RNP RWY 11 APPROACH CODING TABLE											
Fix Name	Fix Type	Path Terminator	Fly-over	Course/Track °M(°T)	Dist (NM)	Turn dir	Alt (ft/FL)	Speed (KIAS)	Mag var	VPA/TCH	RNP value
From IGROM											
IGROM	IAF	IF	–	–	–	–	+FL040	–	-11.0	–	–
DAVLA	IF/IAF	TF	–	205 (193.59)	6.0	L	+2500	–	-11.0	–	1.0
From ELUMO											
ELUMO	IAF	IF	–	–	–	–	+FL040	–	-11.0	–	–
DAVLA	IF/IAF	TF	–	025 (013.58)	6.0	R	+2500	–	-11.0	–	1.0
From DAVLA											
DAVLA	–	–	–	–	–	–	+2500	–	-11.0	–	1.0
BOMDA	FAF	TF	–	115 (103.60)	5.5	–	2000	–	-11.0	–	1.0
S/D 1.5	S/D	TF	–	115 (103.62)	3.8	–	+600	–	-11.0	-3.00/50	0.3
AMAVA	MAPt	TF	Y	115 (103.63)	1.5	–	–	–	-11.0	-3.00/50	0.3
KAPOB	MATF	DF	–	–	–	L*	-FL040	230**	-11.0	–	1.0
IGROM	MAHF	TF	–	295 (283.62)	6.4	–	FL040	–	-11.0	–	1.0

Fix name	Coordinates (WGS-84)
AMAVA	N 12 30 26.16 W 070 02 23.69
BOMDA	N 12 31 41.97 W 070 07 41.98
DAVLA	N 12 32 59.81 W 070 13 09.24
ELUMO	N 12 27 08.32 W 070 14 35.70
IGROM	N 12 38 51.29 W 070 11 42.72
KAPOB	N 12 37 19.89 W 070 05 18.39
S/D 1.5 NM to AMAVA	N 12 30 47.47 W 070 03 53.10

*Climb on extended CL to 800 ft AMSL then turn left
 ** MAX 230 KT through first turn

CHANGES: MAGVAR 2020.